

System Requirements for:

- Flexia Definition Digital, Mediscope Digital
- USB2.0 Frame grabber
- FireWire Frame Grabber
- PCI Frame Grabber
- OptiPix

Component	System recommendation
Computer	Intel Pentium , Intel i3 2.8GHz or higher Recommended systems: Station: HP PRO 34XX MT, Win7P or similar Laptop: HP ProBook 4730s 17.3" HD+ LED or similar
Operating System	Windows XPP, Windows 7P (32 or 64 bit)
Memory	1 GB or higher of RAM, Recommended: 2 GB
Hard disk	Minimum: 10 GB of Free Space Recommended: 100 GB of Free Space
Display	Laptop: 15,6 " / 1366 x 768 (WXGA) PC: 22" /1920 x 1080 (Full HD) Recommended: Laptop: 15,6 " / 1600x900 (HD+) PC: 24" /1920 x 1200
Graphic card	Direct X compatible graphics card is recommended to avoid unnecessary load on the CPU. Example cards are nVidia, G-Force or ATI Recommended: ATI Radeon HD 5000/6000 Series nVIDIA GTX400/500
Other	Three USB2.0 ports. PCI express x1, IEEE 1394 (FireWire) interface, which complies with OHCI (as the PCI/1394o1 or the CBI/1394-1) if your Frame Grabber has Fire Wire interface

Notes:

- Mediscope Digital will only work with Intel CPUs
- PCI Frame Grabber only compatible with desktops that has available PCI express slot. Dell systems are not compatible with PCI Frame Grabber.
- Please avoid using integrated simple graphics card